

Reference: LSC28 Service temperature wine cellar Service range



- + Capacity: 70 L i.e. 28 bottles* or 125 cans**
- Free standing installation
- ♣ Design: black body & silver door frame
- + Cooling system: thermoelectric
- Adjustable temperature range of use: 11 - 18°C
- Electronic regulation
- Thermometer with
- **+** LED lights
- Humidity control: natural (hygrodynamy concept)
- 🛨 1 glass door, anti-UV treated glass

Integrated door panel control

Perfect for storing and serving drinks at the right temperature

No vibrations

Ultra-silent cellar

Small volume, easily adapt to your interior



Our products are manufactured in compliance with European environmental rules.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device

This equipment is designed to be used in an ambient temperature between 16 - 32°C.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 6 shelves. Adding shelves reduce considerably the total capacity.
**Capacity given as an indication with 33cl cans and measured without

shelves.



Reference: LSC28 Service temperature wine cellar Service range



> EQUIPMENTS INCLUDED

- 6 fixed wire shelves
- 1 adjustable foot

> TECHNICAL CHARACTERISTICS

- Energy class: B
- Annual electrical consumption: 164 kWh
- Climatic class: N (16 32°C)
- Noise level: 35 dBVoltage: 220-240 VPower input: 70 W
- Category: 10 Multi-use and other refrigerating

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $50 \times 57.8 \times 76.5$ Net dimensions (WxDxH cm) : $45 \times 52.8 \times 73.5$

Gross weight (kg) : 23.00

Net weight (kg) : 20.00

Full truck (pcs) : 176

Container (pcs) 20' : 132

40' : 288 40' HC : 333

Gencod 3541361811265

> COMPATIBLE ACCESSORIES

Only available in spare parts

Non-contractual pictures Last update: 28/03/2019